





RUBBER ACCESSORIES







NOSINGS



#9 & #10 underlap stair nosing

- Flange-type design for 1/8" low pile carpet; ribbed
- Minimum Installation Radius: 12 ft.
- 5 9-ft. secs. per tube (45 ft.)





ADA



#13 & #14 single flange carpet stair nosing

- Smooth surface; light-duty design; 1/4" butting gauge
- Minimum Installation Radius: 12 ft.
- 5 9-ft. secs. per tube (45 ft.)



ADA



#11 & #12 single flange carpet stair nosing

- Smooth surface; heavy-duty design; 3/8" butting gauge
- Minimum Installation Radius: 12 ft.
- 5 9-ft. secs. per tube (45 ft.)



ADA



#15 double flange carpet stair nosing

- Smooth surface; 3/8" butting gauge
- Minimum Installation Radius: 12 ft.
- 5 9-ft. secs. per tube (45 ft.)





ADA



#16 double flange carpet stair nosing

- Smooth surface; 1/4" butting gauge
- Minimum Installation Radius: 12 ft.
- 5 9-ft. secs. per tube (45 ft.)

ADA



#17 & #18 undercut carpet nosing

- 3/16" undercut; ribbed safety surface
- Minimum Installation Radius: 12 ft.
- 5 9-ft. secs. per tube (45 ft.)

ADA