

PRODUCT DESCRIPTION

Finish & Appearance	Embossed with UV Cured Ceramic Reinforced Urethane
Nominal Dimensions	Lengths from 36" (91.4 cm) to 108" (2.7 m) in 6" (15.2 cm) Increments
Wear Layer Thickness	Nominal 28 mil (0.7 mm)

PRODUCT PERFORMANCE PROPERTIES

ASTM F2169 – Resilient Stair Treads	Type TV, Class 1, Grade 1
ASTM E648 (NFPA 253) – Critical Radiant Flux	Class I, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) – Smoke Density	Passes, ≤ 450
CAN/ULC-S102.2 – Surface Burning	50 Flame Spread Rating; 150 Smoke Development Classification

PRODUCT INSTALLATION & WARRANTY INFORMATION

Required Adhesives	Excelsior EN-610 Epoxy Nose Filler
Recommended Adhesives	Excelsior TP-620 Stair Tread Tape Excelsior PS-525 Modified Pressure Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive
Recommended Installation Accessories	J Channel transition
Product Warranty	10 Year Limited Commercial Warranty

IMAGE & COLOR

Available Colors	026 Gingered Beech	029 Toasted Teak	272 Limed Beige Oak
	040 Limed Gray Oak	045 Steely Ash	
Product Detail	Technical drawing of the Impression LV Stair Tread showing dimensions: 14-1/8" Tread Depth, 8-1/4" Riser Height, and 1/8" (3 mm) Nosing Thickness. A 3D perspective view shows the tread length from 36" to 108" in 6" increments.		

To ensure complete satisfaction, request a physical sample for final approval before placing an order or writing a specification. While we strive for accurate color representation in our marketing materials, variations may occur between printed and electronic media and the actual product.



Impression™ LV Stair Tread

PRODUCT SUBMITTAL

SUPPORT & ADDITIONAL DOCUMENTATION

Product Support Phone & Email	(800) 537 – 9527 / sales@roppe.com
Technical Support Phone & Email	(844) 393 – 4044 / solutions@rhctechnical.com
Product Technical Documentation	www.roppe.com
Associated or Related Documentation	Excelsior EN-610 Epoxy Nose Filler Excelsior TP-620 Pressure Sensitive Tread Tape Adhesive Excelsior PS-525 Modified Pressure Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive Referenced Standards within Technical Documents Technical Bulletin Installation Care & Maintenance Roppe Products Warranty

The contents contained within this Product Submittal (PS) may be utilized or copied into another projected related document, but this original document will remain in effect at the time of product installation, this TDS shall not be supplemented or replaced by the resulting project documentation. Any alterations to the wording or requirements contained in or derived from this document shall void all related warranties.

See installation information and documents for full installation details regarding substrates, job site conditions, & acclimation procedures. The intent of this document is to provide technical and performance properties of the mentioned adhesive as well as define the intended method of installation for the products in which the adhesive is approved for use. Any installation guidelines are to be considered as a starting point at a minimum for a successful installation. We rely on the expertise and professionals that are installing the products to adjust based on site conditions. Anything that appears to be a link, is and leads to additional information if necessary or provides a means of contact in the event there are any additional questions. Prior to acceptance of this document refer to the product website to confirm that you have the most current revision. These products are intended for installation by professionals, prior to use the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability.